

Architec 400[®] EXTRA HEAVY DUTY KNITTED SHADECLOTH

Architec 400[®] is tough under the sun

Architec 400[®] is a 400gsm High Density Polyethylene (HDPE) fabric with an excellent weight to strength ratio. It has very good tensile strength and is extremely resistant to tearing.

Architec 400[®] incorporates the latest in Ultra Violet (UV) stabilizers. These new generation stabilizers extend the UV life of the fabric so that Polyfab can now offer a 15 year warranty – the best industry warranty available (conditions apply). These new UV stabilizers also provide improved color consistency and colorfastness.

Introducing Ovalon[™] our propriety monofilament yarn

Architec 400[®] contains no flat tape.

Instead it is made from a combination of monofilament yarn and our new Ovalon[™] monofilament yarn.

Ovalon[™] provides excellent strength and has minimal stretch in both the Weft and Warp direction of the stitch pattern and will maintain its tension. It also provides very high UV protection over 90%.

With Ovalon[™] you get the strength of monofilament yarns combined with the UV protection of tape.



Architec 400[®] is good under tension

Shadesails using Architec 400[®] should be well designed and engineered to hold the fabric under the tension it deserves.

The fabric should be supported by using appropriate strength poles and footings as determined by a professional engineer, and fabricated and installed by a qualified contractor in accordance with local building codes.

Architec 400[®] is easy to work with

Architec 400[®] has been pre-stentred to reduce shrinkage and improve the stability of the fabric. This process improves the workability of the fabric during the fabrication and installation of the shadesails or shade structure.

Technical Specifications

		WARP	WEFT
Breaking Force (per ASTM D-5034)	lbs	342	270
Elongation at Break (per ASTM D-5034)	%	87	96
Tearing strength (per ASTM D-2261)	lbs	41	38
Mullen Burst (per ASTM D-3786)	lbs/in	Face	593
Ball Burst (per ASTM D-3787)	lbf	Face	450+*

*(Remarks: + Exceeds capacity of tester.)

Colors	Cover Factor	UVR Block %	CALCULATED UVE %	Protection Category	Shade Factor	SRI
Turquoise	92.6	91.0	90.0	Effective	84.7	NA
Porcelain	93.5	92.3	91.0	Very Effective	73.0	87
Cappuccino	96.1	95.8	95.0	Most Effective	86.6	36
Aquamarine	95.2	94.5	93.0	Very Effective	91.0	31
Navy Blue	95.2	94.3	94.0	Very Effective	92.4	NA
Midnight Green	94.7	94.6	93.0	Very effective	93.1	NA
Orange	94.7	94.8	93.0	Very effective	84.7	61
Golden Yellow	91.4	91.4	89.0	Effective	69.1	79
Grape	87.3	87.0	88.0	Effective	77.6	NA
Lime	95.3	95.3	94.0	Very Effective	88.0	56
Slate	95.3	95.2	94.0	Very Effective	95.0	NA
Black	96.6	96.5	95.0	Most Effective	97.2	1

SRI - Solar Reflectance Index (per ASTM E 1980). NA - results not available at the time of print.

According to revised Australian standard AS 4174:2018 for knitted and woven shade fabrics, "The objective of the Standard is to provide requirements for the classification, performance and labelling of knitted and woven shade fabrics for horticultural and human protection uses."

"Shade fabrics shall be classified according to ultraviolet effectiveness (UVE), and human protection category ... shall be designated with a protection category in accordance with Table 3.1."

TABLE 3.1
Ultraviolet Effectiveness (UVE)
Classification System

UVE (%)	Protection category
80.0 to 90.9	Effective
91.0 to 94.9	Very effective
95.0+	Most effective

Architec 400[®] is available in 12 designer colors.



Fire Standard Compliance
Architec 400[®] complies with fire standard: ASTM E-84 (Class 1 or A rating)